

| BEARING NO | OD | ID | Width | Ball Complement | | Maximum speed | | Weight |
|------------|-------|--------|-------|-----------------|--------|----------------|-------------|--------|
| | D(MM) | d (MM) | B(MM) | NO | Size | Grease (r/min) | Oil (r/min) | Kg/pcs |
| S 603 | 9 | 3 | 5 | 7 | 2.000 | 28000 | 36000 | 0.0143 |
| S 604 | 12 | 4 | 4 | 7 | 2.380 | 28000 | 36000 | 0.0020 |
| S 605 | 14 | 5 | 5 | 8 | 2.000 | 39000 | 46000 | 0.0035 |
| S 606 | 17 | 6 | 6 | 6 | 3.175 | 30000 | 38000 | 0.0060 |
| S 607 | 19 | 7 | 6 | 6 | 3.969 | 28000 | 36000 | 0.0080 |
| S 608 | 22 | 8 | 7 | 7 | 3.969 | 26000 | 34000 | 0.0110 |
| S 609 | 24 | 9 | 7 | 7 | 3.969 | 22000 | 30000 | 0.0140 |
| S 6000 | 26 | 10 | 8 | 7 | 4.763 | 20000 | 28000 | 0.0180 |
| S 6001 | 28 | 12 | 8 | 8 | 4.763 | 19000 | 26000 | 0.0200 |
| S 6002 | 32 | 15 | 9 | 9 | 4.763 | 18000 | 24000 | 0.0260 |
| S 6003 | 35 | 17 | 10 | 10 | 4.763 | 17000 | 22000 | 0.0360 |
| S 6004 | 42 | 20 | 12 | 9 | 6.350 | 15000 | 19000 | 0.0690 |
| S 6005 | 47 | 25 | 12 | 10 | 6.350 | 13000 | 17000 | 0.0750 |
| S 6006 | 55 | 30 | 13 | 11 | 7.144 | 12000 | 15000 | 0.1160 |
| S 6007 | 62 | 35 | 14 | 11 | 7.938 | 10000 | 13000 | 0.1550 |
| S 6008 | 68 | 40 | 15 | 12 | 7.938 | 8000 | 11000 | 0.1850 |
| S 6009 | 75 | 45 | 16 | 12 | 9.000 | 7200 | 9000 | 0.2310 |
| S 6010 | 80 | 50 | 16 | 13 | 9.000 | 6400 | 7800 | 0.2500 |
| S 6011 | 90 | 55 | 18 | 11 | 11.112 | 5700 | 7000 | 0.3620 |
| S 6012 | 95 | 60 | 18 | 12 | 11.112 | 5000 | 6300 | 0.3850 |
| S 6013 | 100 | 60 | 18 | 13 | 11.112 | 5000 | 6000 | 0.4080 |
| S 6014 | 110 | 70 | 20 | 13 | 12.000 | 6100 | 7100 | 0.6040 |
| S 6015 | 1150 | 75 | 20 | | | 5700 | 6700 | |